

OCTA LUMINA


120 | 80 | 40 | PLUS

LIGHT FRAMES
WITH A SYSTEM

FAS CINA TING



INTRO

A large, glowing jellyfish is the central focus of the image. It has a translucent, bell-shaped body that glows with a bright, ethereal light, primarily in shades of white and light blue. The jellyfish's internal structure, including its oral arms and possibly its stomach, is visible through the translucent skin. The background is a deep, dark blue, which makes the glowing jellyfish stand out prominently. The overall mood is mysterious and serene.

Light is irresistibly appealing. It has an elementary fascination. Unicellular organisms move towards the light, plants turn towards the sun, and our retina automatically reacts to every light source. It even influences our psyche, our feelings, our health. Hence, the question is not: light or no light? But: how can we use it to shine a light onto our product and company – and create a long-lasting visibility for them? Let us bring some light in the dark.



SET HIGHLIGHTS LIGHTS

EMBEDDED IN THE RETINA
ARE ABOUT 120 MILLION
LIGHT SENSITIVE CELLS.



BRILLIANCE AMBIANCE ATTENTION

FOR YOUR PROJECT

The natural brilliance of light. Increased through high-performance power-LEDs. Ideal light dispersion and neutral color rendering. Additionally, even and absolutely shadow-free illumination. All this makes OCTAlumina more than just illuminated advertisements: a highlight in the most literal sense of the word. Actually, it is not just the outstanding ambiance and excellence that will make your company glow.

OCTALUMINA ILLUMINATION SYSTEM



OCTALumina also sets a shining example in regards to flexibility. Modularly designed, it offers solutions for all spatial requirements. And since the light and electricity components are readily mounted on the frame extrusion, construction and deconstruction are fast and simple. Looking for the perfect presentation and representation system? You found it.

FLEXIBLE MODULAR LARGE-SCALE

FOR FASCINATING ROOM EXPERIENCES



Thinking big? No problem for OCTALumina 120 and 80. The system is flexible so can be extended in height and width. This way, even XXL areas can be used and created – free-standing or mounted onto walls or ceilings. High-quality LEDs with lateral feed-in guarantee for an atmospheric, homogeneous illumination. For sublime room experiences. On a big scale.




**OCTA
LUMINA
120 | 80**

TECHNICAL FEATURES

OCTAlumina 120 | 80




Modern Power-LEDs



Numerous frame colors




Integrated electricity components



120 mm double-sided



Individual suspension



120 mm single-sided



Plug & Play



80 mm single-sided



Silicone edge graphics



Two extrusions. For every requirement.

Our OCTAlumina frames with lateral feed-in are available with 120 mm depth for single or double-sided illumination, or 80 mm depth for single-sided illumination. Both can be powder-coated in all RAL colors – for all spatial and color requirements.

Shining example. Also in regards to quality.

Our high-quality components made from anodized aluminium are dimensionally stable, long-lived, and aesthetic. Lateral feed-in with Power-LEDs ensures a homogeneous illumination and long operating times at low power consumption.

Simple handling? Standard feature.

Our assembly concept in two words: plug & play. Pre-assembled extrusions and simple connectors help save time and money. Our reusable system packaging ensures safe transportation and storage.

Maximum flexibility. Minimum effort.


Free-standing with base plates, wall mounted or suspended from the ceiling; room in room, counter, cabin, or corner solutions: no problem.

THE HUMAN BRAIN CAN PROCESS PICTURES 60,000 TIMES FASTER THAN TEXT.

OCTALUMINA 120 | 80 – FREE-STANDING WITH BASE PLATES

Elegant aluminium surface | without system groove | homogeneous illumination | base plates for stable standing | very fast assembly | single- or double-sided illumination | silicone edge graphics

OCTALUMINA 120 DOUBLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1290.01

Aluminium | 1 free standing 120 mm frame with LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and base plates, for single- or double-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 120 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1290 E.01

Aluminium | 1 free standing 120 mm frame with LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and base plates, for single-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 80 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 890 E.01

Aluminium | 1 free standing 80 mm frame with LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and base plates, for single-sided backlit graphics

Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions in your order



FREE-STANDING WITH BASE PLATES

OCTAlumina 120 | 80 | single-sided | double-sided



I OCTAlumina 120 is also available as a toolless display set **OL 1202** with base plates and transportation bag.


More on page 33.

IT TAKES ABOUT 8 MIN 20 SEC FOR LIGHT TO TRAVEL FROM THE SUN TO EARTH.

OCTALUMINA 120 | 80 – WITHOUT BASE PLATES, FOR INTEGRATION

Elegant aluminium surface | without system groove | homogeneous illumination | can be integrated into, and combined with OCTAwall custom or Maxima light | very fast assembly | single- or double-sided illumination | silicone edge graphics

OCTALUMINA 120 DOUBLE-SIDED | CUSTOM SIZE




OL 1291.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, without base plates, for single- or double-sided backlit graphics

Without fabric/print


Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions and position of cable outlet in your order



Maximum height
or width 3000 mm

OCTALUMINA 120 SINGLE-SIDED | CUSTOM SIZE




OL 1291 E.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, without base plates, for single-sided backlit graphics

Without fabric/print


Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions and position of cable outlet in your order



Maximum height
or width 3000 mm

OCTALUMINA 80 SINGLE-SIDED | CUSTOM SIZE




OL 891 E.01

Aluminium | 1 frame with 80 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, without base plates, for single-sided backlit graphics

Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled


Please state frame dimensions and position of cable outlet in your order



Maximum height
or width 3000 mm

INTEGRATED WITHOUT BASE PLATES

OCTAlumina 120 | 80 | single-sided | double-sided




This L-shaped construction can be realized with a square extrusion M 1020 or M 230.



OCTALUMINA 120 | 80 – VERTICAL CEILING SUSPENSION

Elegant aluminium surface | without system groove | homogeneous illumination | adaptor for vertical ceiling suspension | very fast assembly | single- or double-sided illumination | silicone edge graphics

OCTALUMINA 120 DOUBLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1292.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and eyebolts OL 220 for vertical ceiling suspension (number according to frame size), for single- or double-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions and position of eyebolts in your order



OCTALUMINA 120 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1292 E.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and eyebolts OL 220 for vertical ceiling suspension (number according to frame size), for single-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions and position of eyebolts in your order



OCTALUMINA 80 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 892 E.01

Aluminium | 1 frame with 80 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and eyebolts OL 220 for vertical ceiling suspension (number according to frame size), for single-sided backlit graphics

Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions and position of eyebolts in your order



VERTICAL CEILING SUSPENSION

OCTAlumina 120 | 80 | single-sided | double-sided



**THE SHORTEST FLASH IN THE
WORLD ONLY LIGHTS UP FOR
A BILLIONTH OF A SPLIT
SECOND.**


All frame
extrusions are
sent out in special
reusable packaging
to prevent damage.



OCTALUMINA 120 | 80 – HORIZONTAL CEILING SUSPENSION AND WALL MOUNTING

Elegant aluminium surface | without system groove | homogeneous illumination | adaptor for horizontal ceiling suspension or wall mounting | very fast assembly | single- or double-sided illumination | silicone edge graphics

OCTALUMINA 120 DOUBLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1293.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and universal retainers OL 230 for horizontal ceiling suspension or wall mounting (number according to frame size), for single- or double-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 120 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 1293 E.01

Aluminium | 1 frame with 120 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and universal retainers OL 234 for horizontal ceiling suspension or wall mounting (number according to frame size), for single-sided backlit graphics


Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 80 SINGLE-SIDED | CUSTOM SIZE



Maximum height
or width 3000 mm


OL 893 E.01

Aluminium | 1 frame with 80 mm extrusion width, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug and universal retainers OL 236 for horizontal ceiling suspension or wall mounting (number according to frame size), for single-sided backlit graphics

Without fabric/print

Measurements for prints = outer frame dimensions
Frames are delivered disassembled


Please state frame dimensions in your order



HORIZONTAL CEILING SUSPENSION + WALL MOUNTING

OCTAlumina 120 | 80 | single-sided | double-sided

HUMANS CAN DISTINGUISH
ABOUT 20 MILLION
DIFFERENT COLORS.



i The **OL 230**, **OL 234** and **OL 236** adaptor can be used for both horizontal ceiling suspension or wall mounting.




OCTALUMINA 120 CORNER SOLUTION

Elegant aluminium surface | without system groove | homogeneous illumination | corners with no visible edges | very fast assembly | single- or double-sided illumination | silicone edge graphics



! The silicone edge has to be cut at a 45° angle (for instructions see technical brochure)

OCTALUMINA 120 CORNER SOLUTION | L-SHAPED



! Maximum height or width 3000 mm


OL 1261.01

Aluminium | L-shaped corner structure with 120 mm extrusion width for corners with no visible edges, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, for single- or double-sided backlit graphics


Without fabric/print

Measurements for prints = see technical brochure
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 120 CORNER SOLUTION | U-SHAPED



! Maximum height or width 3000 mm


OL 1262.01

Aluminium | U-shaped corner structure with 120 mm extrusion width for corners with no visible edges, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, for single- or double-sided backlit graphics

Without fabric/print

Measurements for prints = see technical brochure
Frames are delivered disassembled

Please state frame dimensions in your order



OCTALUMINA 120 CORNER SOLUTION | RECTANGLE



! Maximum height or width 3000 mm


OL 1264.01

Aluminium | Rectangular corner structure with 120 mm extrusion width for corners with no visible edges, LED modules and LED power supply unit mounted, incl. 2 m cable with Schuko plug, for single- or double-sided backlit graphics

Without fabric/print


Measurements for prints = see technical brochure
Frames are delivered disassembled

Please state frame dimensions in your order



CORNER SOLUTION


OCTAlumina 120 | single-sided | double-sided




**THE BRIGHTEST GALAXY IN THE
UNIVERSE IS AS BRIGHT AS 300
TRILLION SUNS.**

ULTRA-THIN PRESTIGIOUS BRIGHT

A BIG IMPACT EVEN IN THE SMALLEST ROOM



There are rooms. And there are rooms with an impact. Thanks to one simple highlight – like the OCTAlumina 40. The system can captivate with its homogeneous and shadow-free illumination thanks to the LEDs on the rear cover. Just as captivating: its decorative and representative sides, which immediately catch the eye. Whether it is wall mounted, suspended from the ceiling, or a free-standing corner: just plug it in. Done. Brilliant.





Modern Power-LEDs



Numerous frame colors



Plug & Play




Integrated PSU


OCTA LUMINA 40



Silicone edge graphics



40 mm with system groove



40 mm without system groove

TECHNICAL FEATURES

OCTAlumina 40

With or without system groove. Whatever you need.

The OCTAlumina 40 is available in standard sizes DIN A0 and DIN A1 without, and in 950 × 2480 mm with system groove. Individual sizes are possible by request.

Compelling quality. Amazing luminosity.

Our high-quality components are pre-assembled with Power-LEDs, ensuring a brilliant illumination with radiant colors. Other advantages: their longevity and low energy requirements.

Handling: fast and simple.

The OCTAlumina 40 frames are supplied completely pre-assembled; no further assembly required. Your frame is ready for immediate use.

Main application: everything.

Fairs, events, POS, or exhibitions: OCTAlumina 40 can be used for all kinds of decorative or presentation purposes – even in combination with OCTAwall or Maxima 40. The only thing you will have to decide: standalone, suspended, or mounted?

NEW! The invisible PSU.

The slimline power supply unit. Your advantage: an undisturbed, appealing look, because the PSU is integrated in the frame and invisible from the outside. This also makes a costly hidden installation of the PSU into the wall a problem of the past. Compact and simple to install.





OCTALUMINA 40 WITH SYSTEM GROOVE

Elegant aluminium surface | with system groove | very high luminosity | homogeneous illumination | readily assembled | single-sided illumination | silicone edge graphics

OCTALUMINA 40 WITH SYSTEM GROOVE




Individual sizes are possible by request

OL 415.01

Aluminium | 1 frame with 40 mm extrusion width, with system groove, with borings on both sides to mount other frames, aluminium composite panel with LED modules mounted, incl. 2 m cable with Schuko plug, with adjustable foot, external PSU, for single-sided backlit graphics

Without fabric/print

Outer frame dimensions: W 950 × H 2480 mm
Measurements for prints = outer frame dimensions



OCTALumina 40



THE ENERGY EFFICIENCY FOR FIREFLIES IS 95%.

OCTALUMINA 40 WITHOUT SYSTEM GROOVE

Elegant aluminium surface | without system groove | very high luminosity | homogeneous illumination | readily assembled | single-sided illumination | silicone edge graphics | integrated power supply unit

OCTALUMINA 40 WITHOUT SYSTEM GROOVE




OL 400.01

Aluminium | 1 frame with 40 mm extrusion width, without system groove, aluminium composite panel with LED modules mounted, incl. 2 m cable with Schuko plug, integrated PSU, for single-sided backlit graphics

Without fabric/print

Outer frame dimensions: W 1189 × H 841 mm (DIN A0)
Measurements for prints = outer frame dimensions



OCTALUMINA 40 WITHOUT SYSTEM GROOVE




OL 401.01

Aluminium | 1 frame with 40 mm extrusion width, without system groove, aluminium composite panel with LED modules mounted, incl. 2 m cable with Schuko plug, integrated PSU, for single-sided backlit graphics

Without fabric/print

Outer frame dimensions: W 841 × H 594 mm (DIN A1)
Measurements for prints = outer frame dimensions






MULTIFUNCTIONAL PRACTICAL SOPHISTICATED

A BIGGER DIVERSITY FOR SPATIAL PRESENTATIONS

OCTAlumina stands for individuality and flexibility. But also for practicality and simplicity. Hence, we added a collection of multifunctional extra components for immediate use. Same material. Same appearance. Bigger diversity.





OCTALUMINA CEILING LAMP

Homogeneous illumination | no system groove | for horizontal ceiling suspension | for single-sided illumination | silicone edge technology


OCTALUMINA CEILING LAMP



OL 480.23

Aluminium, black | 1 ceiling lamp with 40 mm extrusion width, with suspension, aluminium composite panel with LED modules mounted, incl. white fabric and cable with Schuko plug, Ø 800 mm, total height 900 mm

Without print



SPECIALS

OCTALumina ceiling lamp | OCTALumina cube



i The silicone edge has to be cut at a 45° angle (for instructions see technical brochure)

OCTALUMINA CUBE

Homogeneous illumination | corners with no visible edges | very fast assembly | multi-sided illumination | silicone edge graphics

OCTALUMINA CUBE




OL 690.01

Aluminium | cube solution for ceiling suspension, depending on size with lighting element straight T-shaped, or cone-shaped, without accessories, up to 2500 mm edge length

Without fabric/print

Please state dimensions in your order



i Maximum edge length for the cube is 2500 mm

The silicone edge corners have to be cut at a 45° angle (for instructions see technical brochure)



OCTALUMINA BAR TABLE

Homogeneous illumination | corners with no visible edges | very fast assembly | convenient height | multi-sided illumination | silicone edge graphics

OCTALUMINA BAR TABLE




OL T50.90

Aluminium | bar table with 4 illuminated sides, corners with no visible edges, with tabletop, Delivery without chairs

Without fabric/print

Dimensions: W 570 × H 1031 × D 570 mm
Outer frame dimensions: W 498 × H 998 mm
Measurements for prints = outer frame dimensions



IT IS A PROVEN FACT THAT
LIGHT CAN HAVE A POSITIVE
IMPACT ON OUR PSYCHE AND
PERFORMANCE.



OCTALUMINA 120 TOOLLESS

Elegant aluminium surface | without system groove | deconstructable frame | homogeneous illumination | toolless | very fast assembly | with transportation bag | single- or double-sided illumination | silicone edge graphics

OCTALUMINA 120 TOOLLESS




OL 1202.01

Aluminium | 1 free standing 120 mm frame (deconstructable), toolless, with LED modules single-sided and LED power supply unit mounted, incl. 2 m cable with Schuko plug and base plates, for single or double-sided backlit graphics, incl. transportation bag OL 901

Without fabric/print

Dimensions: W 800 × H 1800 mm
Outer frame dimensions: W 800 × H 1800 mm
Measurements for prints = outer frame dimensions
Frame elements are delivered disassembled in the transportation bag



i OL 1202-B
with double-sided
LED placement



OCTALUMINA FABRIC COUNTER

Elegant aluminium surface | OCTALumina front frame | homogeneous illumination | convenient height | foldable construction | silicone edge graphic

OCTALUMINA FABRIC COUNTER


OL C800.90

Modular counter, incl. 2 shelves, OCTALumina front frame, fabric wing doors without illumination, pre-assembled LED modules and power supply unit, space-saving thanks to foldable construction, easy assembly

Without fabric/print

Dimensions: W 900 mm × H 900 mm × D 440 mm
 Outer frame dimensions front: W 900 mm × H 900 mm
 Outer frame dimensions side: W 440 mm × H 900 mm

Measurements for prints = outer frame dimensions + 5 mm



The silicone edge has to be cut at a 45° angle (for instructions see technical brochure)

SPECIALS

OCTALumina fabric counter | OCTALumina counter

**COMPARED TO
REGULAR LIGHT BULBS,
LEDS NEED 90% LESS
ENERGY AND LIVE
25 TIMES AS LONG.**



OCTALUMINA COUNTER

Elegant aluminium surface | OCTALumina 80 front frame | homogeneous illumination | color: white | convenient height | lockable wooden cabinet with wing doors | B1 certified | silicone edge graphic

OCTALUMINA COUNTER




OL C500.90

Modular counter with lockable wing doors, Bs1d0 certified, incl. 1 shelf, OCTALumina 80 (single-sided) front frame, pre-assembled LED modules and power supply unit, color: white (RAL 9010), space-saving thanks to foldable side panels, easy assembly

Without fabric/print

Dimensions: W 1000 × H 1200 × D 448 mm
Outer frame dimensions: W 1000 × H 1129 mm

Measurements for prints = outer frame dimensions




i Counter without doors:
OL C505

Also available
separately:
Door set **OL C580**

DIVERS 3-DIMENSIONAL EXPRESSIVE

A PLUS ON ALL LEVELS

More freedom. Less profile edges. OCTAlumina plus. Additional effects and designs make OCTAlumina plus something special: different layers of fabric and materials create a three-dimensional impression that changes with the viewing angle. Thanks to its three-dimensional design, OCTAlumina plus enables the realization of innovative illuminated room designs with a modern look in proven OCTANORM quality.






**OCTA
LUMINA
PLUS**

TECHNICAL FEATURES

OCTAlumina plus



Several fabric grooves



90° corner



invisible profile edges

1 profile. 2 fabric grooves on front. 3 dimensions.

Fitted with another fabric groove, OCTAlumina plus offers new possibilities. By playing with two layers and different fabrics, you can create impressive 3D effects.

Slanted groove. Without profile edges.

Visible frame edges are a thing of the past now. The new profiles allow for a complete cladding with tension fabric, even of edges. Thanks to the new groove, slanted at 30°, the silicone edges are firmly tightened around the profile.

The solution for fabric corners.

OCTAlumina plus completely focuses on the image. Even in corners. Graphics are only separated by a 2 mm thin profile edge in the corners for a virtually seamless picture.

Illuminated room. Illuminated door.

Build enclosed, freestanding rooms with OCTAlumina plus. If desired, also add flush-mounted illuminated doors. Create an impressive ambience that captivates the visitor and creates a lasting effect.



OCTALUMINA PLUS EXTRUSION

Homogeneous illumination | no system groove | for multiple fabric layers | no visible profile edges | for single-sided illumination | silicone edge technology


FRAME EXTRUSION



U 1060.01

Aluminium | Extrusion for several fabric layers to create a three-dimensional effect, slanted groove without visible profile edges, profile depth 120 mm

Without fabric/print



We recommend elastic fabrics.


CORNER EXTRUSION



U 1063.01

Aluminium | Extrusion for several fabric layers to create a three-dimensional effect, slanted groove without visible profile edges, for the construction of 90° corners in connection with frame extrusion U 1060, profile depth 120 mm

Without fabric/print



EXTRUSIONS | ILLUMINATED DOOR

OCTAlumina plus



OCTALUMINA PLUS ILLUMINATED DOOR

Homogeneous illumination | With electronic door lock | RFID access control | For single- or double-sided illumination | Silicone edge technology

DOOR ELEMENT




OL 895.01

Aluminium | door element, illuminated, DIN left or DIN right, opens outwards, incl. electronic door lock, RFID access control, incl. 10 chip cards


Without fabric/print

Version:
OL 895 - without illumination
OL 895A - incl. illumination 3 m height
OL 895B - incl. illumination 5 m height

Outer frame dimensions: W 896 × H 1991 mm
Measurements for prints = outer frame dimensions



! Attention: electronic door lock opens automatically in the event of a power cut!



EXHIBITION SYSTEMS
PROJECT SOLUTIONS
PRESENTATION
INTERIOR DESIGN
CLEANROOM SYSTEMS

OCTANORM® Germany
Head Office

Raiffeisenstraße 39
70794 Filderstadt
T. +49 711 77003-0
F. +49 711 77003-53
info@octanorm.de
www.octanorm.com

EUROPE

OCTANORM® Belgium
T. +32 2 344 9880
www.octanorm.be

OCTANORM® France
T. +33 1 4695 5406
www.octanorm.fr

OCTANORM® UK
T. +44 20 85 45 2945
www.octanorm.co.uk

OCTANORM® Hellas
T. +30 2310 79 6521
www.octanorm.gr

OCTANORM® Italia
T. +39 02 9645 1966
www.octanorm.it

OCTANORM® Nederland
T. +31 50 309 5133
www.octanorm.nl

OCTANORM® Polska
T. +48 22 773 0350
www.octanorm.pl

OCTANORM® Adria
T. +386 590 56301
www.octanormadria.com

OCTANORM® Espana
T. +34 930 019 424
www.octanorm.es

OCTANORM® Nordic
T. +46 8 621 6500
www.octanorm.se

OCTANORM® Russia
T. +7 495 565 7920
www.octanorm.ru

AMERICA

OCTANORM® North America
T. +1 770 7 32 1520
www.octanormna.com

OCTANORM® México
T. +52 55 5804 6325
www.octanorm.com.mx

OCTANORM® Brasil
T. +55 11 3807 2552
www.octanorm.com.br

OCTANORM® Argentina
T. +54 11 43 12 4000
www.octanorm.com.ar

AFRICA

OCTANORM® South Africa
T. +27 11 433 2010
www.octanorm.co.za

MIDDLE EAST

OCTANORM® Emirates
T. +971 4 340 6888
www.octanormemirates.net

AUSTRALIA

OCTANORM® Australia
T. +61 3 8773 8550
www.octanorm.com.au

ASIA

OCTANORM® Japan
T. +81 45 511 8144
www.octanorm.jp

OCTANORM® China
T. +86 512 6283 3336
www.octanorm.cn